

IMAGE FORMING APPARATUS

The present invention relates to an image forming apparatus such as a copying machine, and in particular to a digital copying machine which forms an optimal image using a density histogram of a document or original image.

A so-called automatic exposure adjusting function where an optimal image is obtained by changing brightness of a document-illuminating lamp while detecting a density of a document or original image is a general function in an analog copying machine. In order to realize a function similar to the automatic exposure adjusting function in such an analog copying machine, such a measure is employed in a conventional digital copying machine that an optimal density is reproduced for each of documents of various kinds.

A method where an optimal image is obtained using a pixel density histogram indicating the number of existing pixels on a document image corresponding to each density is commonly employed in conventional machines. However, in order to perform image processing for improving image quality by pre-scanning a document and preparing a density histogram using all sampled pixels, not only a large amount of memory but also a large-scale of hardware and a considerably long

processing time are required. Also, in a case that the pre-scanning processing is performed, scan must be performed twice, which results in reduction in productivity.

5 In order to solve this problem, in Jpn. Pat. Appln. KOKAI Publication No. 8-88772, such a technique has been disclosed that, in a real time automatic density adjusting system, histograms for respective image lines read by a scanner are accumulated and a
10 reference value for range correction is sequentially changed on the basis of the result of the accumulation to perform an automatic density adjusting processing for each document. The reference value for range correction is a reference value applied when the
15 density of image to be printed is corrected on the basis of a background density and a character or letter density of a document.

 In the system disclosed in the above publication, the reference value for range correction is
20 sequentially changed for each image line on the basis of the histograms accumulated. Therefore, even in a case of characters or photographs with the same density in one document, information about the accumulated histograms thereof varies according to the status of
25 a document image around the characters or photographs, which results in difference in reference value for range correction. Accordingly, it has been difficult

to achieve even density reproduction in a document
image. When the reference value for range correction
is fixed in order to achieve even density reproduction
in a document image, of course, it becomes impossible
5 to achieve an optimal density adjustment to another
document with a different background density.

Also, in Jpn. Pat. Appln. KOKAI Publication
No. 8-317149, a method or process where any pre-
scanning is not performed as image data is stored
10 in RAM has been disclosed. In this method, however,
a background processing is not performed as image
processing but it is performed as circuit control using
a data comparator. In this publication, therefore,
it has been impossible to remove a background and
15 reproduce a character(s) densely, which can be achieved
in a range correction processing performed as the image
processing.

BRIEF SUMMARY OF THE INVENTION

An object of the present invention is to provide,
20 in a digital copying machine, an automatic density
adjustment processing system where even density
reproduction suitable for a kind of a document to
be processed can be realized without processing any
pre-scanning.

25 In order to achieve the above object, according to
one aspect of the present invention, there is provided
an image processing apparatus comprising: a scanner

section which reads a document in a main scanning
direction and in a sub-scanning direction to provide
image data indicating a density of each pixel within a
document image for each image line in the main scanning
5 direction; a storing section which stores the image
data provided from the scanner in a memory; a histogram
creating section which takes in the image data provided
from the scanner for each image line and creates a
density histogram of the document image on the basis of
10 image data corresponding to a predetermined number of
image lines; a correction reference value calculating
section which calculates a set of correction reference
values for pixel density correction using the density
histogram created in the histogram creating section;
15 a pixel density correcting section which reads out the
image data stored in the memory and performs correction
of a pixel density indicated by the image data on
all the read image data using the set of correction
reference values calculated in the correction reference
20 value calculating section; and image forming means
which forms an image from the pixel density corrected
in the pixel density correcting section. The predeter-
mined number of image lines is equal to or less than
the number of all the image lines on the document image
25 read by the scanner section.

In the above aspect, image data is accumulated in
a delay memory during real time processing of one scan

of a document at the scanner section and simultaneously
a density histogram of a document image is created
using partial image data of the document image, and
a set of reference values for range correction are
5 determined using the density histogram. An automatic
density adjusting processing is performed on all the
image data read out from the delay memory using a set
of reference values for range correction. Therefore,
according to the aspect, the automatic density
10 adjustment processing corresponding to the kind of the
document can be performed without deterioration of
throughput in a copying machine and an even density
reproduction can be realized within a document.

According to another aspect of the present
15 invention, there is provided an image processing system
comprising: a storing section which stores image data
indicating a density of each pixel within a document
image into a memory; a histogram creating section which
takes in the image data indicating the density of each
20 pixel within the document image and creates a density
histogram of the document image on the basis of
a predetermined amount of image data; a correction
reference value calculating section which calculates
a set of correction reference values for pixel density
25 correction using the density histogram created in
the histogram creating section; and a pixel density
correcting section which reads out image data stored in

the memory and corrects pixel density indicated by the image data regarding all the image data read out using the set of correction reference values calculated in the correction reference value calculating section.

5

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a sectional view showing an interior structure of a digital copying machine to which the present invention is applied;

10

FIG. 2 is a block diagram showing a configuration of a control system for the digital copying machine to which the present invention is applied;

FIG. 3 is a block diagram showing a configuration of an image processing section according to the present invention;

15

FIG. 4A is a graph showing one example of a density histogram, and FIG. 4B is a graph showing one example of a density histogram after range correction;

20

FIG. 5 is a flowchart showing an image processing operation according to one embodiment of the present invention; and

FIG. 6 is a flowchart showing an image processing operation according to another embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

25

One embodiment of the present invention will be explained below with reference to the drawings.

FIG. 1 is a sectional view showing an interior

structure of a digital copying machine 10 to which the present invention is applied. Provided in the digital copying machine 10 are a scanner section 4 which functions as reading means and a printer section 6 which functions as image forming section, which will be described later.

The scanner section 4 includes a document stand 12, first and second carriages 27, 28, a focusing or image forming lens 32 and a CCD sensor 34. Mounted on the first carriage 27 are an exposing lamp 25 and a first mirror 26. Mounted to the second carriage 28 are second and third mirrors 30, 31. The first and second carriages 27, 28 are moved in parallel to the document stand 12, and the second carriage 28 is moved at a speed of 1/2 of the first carriage 27.

In the scanner section 4, a document D put on the document stand 12 is illuminated by the exposing lamp 25 and reflected light from the document D is guided up to a light receiving face of the CCD sensor 34 via the first to third mirrors 26 to 31 and the focusing lens 32, so that a line-shaped reflected light (image line) focused on the light receiving face is subjected to photo-electric conversion.

On the other hand, the printer section 6 includes a laser exposing device 40, a photosensitive drum 44, paper cassettes 52 to 55, a fusing device 60 and a finisher 150.

In the laser exposing device 40, laser beam emitted from a semiconductor laser 41 which is ON/OFF-controlled according to image information or the like from the scanner section 4 is guided to the
5 photosensitive drum 44 via a rotating polygon mirror 36 and a laser optical system 42 to form an electrostatic latent image on a surface of the photosensitive drum 44.

An electron charger 45, a developing device 46,
10 a peeling-off charger 47, a transfer charger 48, a peeling-off claw 49, a cleaning device 50, a charge remover 51 are arranged around the photosensitive drum 44 in this order, and a toner image corresponding to the electrostatic latent image on the photosensitive
15 drum 44 is transferred on a paper P fed from, for example, the paper cassette 55.

The paper on which the toner image has been transferred is conveyed to the fixing device 60 via a conveying path 58, and the toner image is fixed on
20 the paper by a fixing lamp 60a and a heat roller 60b of the fixing device 60 to be ejected or discharged onto a single tray of the finisher 150 via an ejecting port 61.

FIG. 2 is a block diagram schematically showing
25 configuration of a control system of the digital copying machine to which the present invention is applied.

The digital copying machine comprises a main control section 90 controlled by a system CPU 91, the scanner section 4 controlled by a scanner CPU 100, the printer section 6 controlled by a printer CPU 110, and a control panel 80 controlled by a panel CPU 83.

The control panel 80 includes a key pad 82, the panel CPU 83, and a liquid crystal display section 84. A setting screen for printing conditions and the like are displayed on the liquid crystal display section 84, and the panel CPU 83 receives data about printing conditions key-input by a user via the key pad 82 to transfer the key-input data to the main control section 90 and perform displaying on the liquid crystal display section 84.

The main control section 90 includes the system CPU 91, a ROM 92, a RAM 93, a NVRAM (Nonvolatile RAM) 94, a common RAM 95, an image processing section 96, a printer font ROM 121, a horizontal synchronizing signal generating circuit 123, an image transferring clock generating circuit 124, and a facsimile interface 130.

The system CPU 91 uses the RAM 93 as a working area to control the entire of the main control section 90 according to a control program including the present invention stored in the ROM 92 and the key-input data received from the control panel 80. The system CPU 91 transmits operation instructions to the printer 6 (printer CPU 110) and the scanner 4 (scanner CPU 100),

and the printer 2 and the scanner 4 return back their statuses to the system CPU 91.

5 The NVRAM 94 is a non-volatile memory backed up by a battery (not shown), so that the data in the NVRAM 94 can be reserved even when power is turned off. Also, the NVRAM 94 stores default values (initial set values) for hardware elements constituting a reproducing or copying (PPC) function, a FAX function and the like therein. The common RAM 95 is used so as to perform
10 bi-directional communication between the system CPU 91 and the printer CPU 110.

 The image processing section 96 performs such image processings by the present invention as range correction, trimming, masking and the like on image
15 data input from the scanner section 4 and the like. The printer font ROM 121 stores font data corresponding to code data such as character code or the like therein.

 A printer controller 99 receives code data such
20 as character code or the like from an external device such as a personal computer or the like via a LAN. The printer controller 99 develops the code data with a character size and at a resolution according to data indicating the character size and the resolution
25 attached to the code data using font data stored in the printer font ROM 121 to store the developed code data in a page memory 98.

The horizontal synchronizing signal generating circuit 123 generates horizontal synchronizing signal synchronized with rotation of the polygon mirror 36. The image transferring clock generating circuit 124
5 generates a image transferring clock which controls a timing for transferring image data.

The printer section 6 includes the printer CPU 110 which controls the entire of the printer section 6, a ROM 111 in which a control program and the like have
10 been stored, a RAM 112 for data storage, a LD drive circuit 113 which performs on/off-control of emission from the semiconductor laser 41, a polygon motor drive circuit 114 which controls rotation of a polygon motor 37 in the laser exposing device or laser unit 40,
15 a paper conveying section 115, a developing process section 116, a fixation control section 117, an option section 118, and a main motor drive circuit 119.

The scanner section 4 includes the scanner CPU 100, a ROM 101, a RAM 102, a CCD driver 103, a scanner
20 motor driver 104, and an image correction section 105. The scanner CPU 100 controls the scanner section 4 wholly, the ROM 101 stores a control program and the like therein, and the RAM 102 is used to temporarily store data therein. The CCD driver 103 drives the CCD
25 sensor 34, and the scanner motor driver 104 controls rotation of a drive motor 38 which moves the first and second carriages 27 and 28 for the exposing lamp 25

and the mirrors 26, 30, 31 and the like. The image correction section 105 includes an A/D converting circuit which converts an analog signal from the CCD sensor 34 to a digital signal and a shading correction circuit for correcting a variation of a threshold level to an output signal from the CCD sensor 34 due to a variation of the CCD sensor 34 itself or a temperature change of an ambient atmosphere.

FIG. 3 is a block diagram showing a configuration of the image processing section 96 according to the present invention. The image processing section 96 includes a memory controller 97, the page memory 98, the reference value calculating section 100, a low pass filter 101, a high pass filter 102, a range correction section 103, an amplifier 104, an adder 105, a scaling section 106, a correction section 107, and a gradation processing section 108.

Document image data read by the scanner section 4 is supplied to the memory controller 97 and the reference value calculating section 100. The reference value calculating section 100 creates a density histogram on the basis of image data from the scanner section 4 to calculate a reference value for range correction (describe later) from the density histogram.

The memory controller 97 stores image data from the scanner section 4 into the page memory 98. The memory controller 97 starts reading-out of the

image data stored in the page memory 98 after the reference value has been determined in the reference value calculating section 100. The image data read out from the page memory 98 is filtrated by the low pass
5 filter 101 to be supplied to the range correction section 103 and the high pass filter 102.

The data filtrated by the high pass filter 102 is multiplied k-fold by the amplifier 106 to be supplied to the adder 105. The adder 105 adds the image data
10 subjected to range correction in the range correction section 103 and the image data amplified by the amplifier 106 to each other. The image data supplied from the adder 105 is subjected to an enlarging processing or a reducing processing in the scaling
15 section 106 to be supplied to the correction section 107. The correction section 107 performs γ correction of the scanner section 4 or the printer section 6 and the entire density adjustment. The gradation processing section 108 performs gradation processing
20 such as a screening processing or the like on the image data corrected in the correction section 107. The image data processed in the gradation processing section 108 is supplied to the LD drive circuit 113 (refer to FIG. 2) via an image data bus.

25 The density histogram created in the reference value calculating section 100 will be explained now.

FIG. 4A is a graph showing one example of

a density histogram. For example, assuming that an image of A4 size is read in at a resolution of 400 dpi, the total pixel number G is expressed by the following equation.

5
$$G = 210 * 297 * (400/25.4)^2$$

Each pixel of the total pixel number G has a density, where the density is expressed by 8 bits (256 steps). The horizontal axis in FIG. 4A indicates the density, or pixel value, and the vertical axis
10 therein indicates the frequency (the number of pixels) indicating the numbers of pixels with respective densities. Incidentally, in order to reduce hardware scale and processing time, the reference value calculating section 100 creates a density histogram by
15 dividing the density into 16 stages to simplify the density of 256 stages into 16 stages. That is, the lower 4 bits in the pixel values of 8 bits are ignored.

In general, in a case of a document such as a newspaper, since there is a considerable amount
20 of background density, one mountain is formed in a background density portion as shown with "R" in FIG. 4A, and one mountain is also formed in a character density portion as shown with "S". Here, in the analog copying machine, the background density portion can
25 be eliminated by controlling an exposure lamp, but in the digital copying machine, a similar effect can be achieved by a method such as described below.

According to explanation through a simple example,
the densities D_W and D_B which correspond to the peak
points of the mountain "R" and the mountain "S" shown
in FIG. 4A, respectively are obtained and the following
5 calculation is made so that the density histogram is
converted to a distribution as shown in FIG. 4B. Here,
the densities D_W and D_B are reference values applied in
a case of performing the range correction, and they are
called white side reference value and black side
10 reference value, which are calculated in the reference
value calculating section 100.

$$D_N = (D_I - D_W) * FF[H] / (D_B - D_W)$$

Where D_N is a corrected pixel density, D_I is
an input pixel density, an $FF[H]$ is the maximum pixel
15 density indicated by hexadecimal number. That is, the
range (density width) between R and N in FIG. 4A is
spread to a range of 0 to $FF[H]$. The range correction
section 103 performs such correction on input image
data.

20 An operation of image processing according to
the present invention will be explained now. FIG. 5 is
a flowchart showing an image processing operation
according to one embodiment of the present invention.

After the system CPU 91 sends a scan start command
25 to the scanner CPU 100, it sets the number M of image
lines for calculation used for calculating the
reference value for range correction (Steps S1 and S2).

The number M of image lines is the number of scanning lines equal to or less than that of one page of a document, for example, it is 3,000. This number of 3,000 corresponds to the number of image lines read in
5 by the CCD line sensor 34 in a case that a document is read by a size of about 12 cm along the sub-scanning direction at a resolution of 600 dpi. That is, the data corresponding to the number M of image lines is data including a partial area of a document image.
10 According to increase in the number of image lines for calculation, a histogram reflecting the density of a document more accurately can be created, but a processing time is increased. Accordingly, the number M of image lines must be set to an appropriate value
15 according to the size of a document to be scanned.

The image data of the document read by the scanner section 4 is output to the memory controller 97 and the reference value calculating section 100. The memory controller 97 starts writing operation of the image
20 data into the page memory 98 (Step S3).

The reference value calculating section 100 takes in the image data from the scanner section 4, creation of such a density histogram as shown in FIG. 4A is started (Step S4). At this time, in the reference
25 value calculating section 100 and the memory controller 97, 1 is added to the number N of taken-in lines each time when a histogram is created by taking in image

data corresponding to one image line, as shown in Step S5.

In this embodiment, the reference value calculating section 100 multiplies the frequency of the histogram created up to the preceding image line (the number of pixels corresponding to each image density) by a weighting coefficient corresponding to the number N of taken-in line, it multiplies the frequency of the histogram about the current image line by another weighting coefficient corresponding to the number N of line, and it creates a density histogram by adding these multiplied results to each other. Therefore, the total amount of frequency data constituting the density histogram created by taking in each image line is kept constant. Incidentally, a hardware configuration for creating this histogram has been explained in US Patent No. 5,724,444.

Furthermore, the reference value calculating section 100 calculates a white side reference value D_W indicating a background density and a black side reference value D_B indicating a character density which are reference values for range correction such as shown in FIG. 4A (Step S6). Each time when such reference values are calculated, the reference value calculating section 100 makes a determination about whether the number N of taken-in lines coincides with the number M of lines for calculation (Step S7). When the number N

of taken-in lines does not coincide with the number N,
a flow returns back to Step S4, and image data corre-
sponding to the next one image line is taken in the
reference value calculating section 100, so that
5 creation (updating) of the histograms and calculation
(updating) of the reference values are repeated.

In the memory controller 97, when the number N of
taken-in lines coincides with the number N (Yes in Step
S7), reading-out of the document image data stored in
10 the page memory 98 is started (Step S8). That is, the
image data is stored in page memory and the timing for
reading-out thereof is delayed by a time corresponding
to the M lines so that the memory controller 97 delays
the image data in the page memory 98. At this time,
15 reading of the document image at the scanner section 4
is performed subsequently so that the page memory 98
conducts both writing-in and reading-out of the image
data.

Incidentally, in Step S3, when the image data is
20 written in the page memory 98, the system CPU 91 may
control the reference value calculating section 100
and the memory controller 97 such that, when the
data corresponding to the number M (a predetermined
number) of image lines for calculation has been stored
25 in the page memory 98, reading-out of data starts
from the image data which has been first written in.
Alternatively, as means for delaying the image data,

a FIFO (first-in first-out) memory which can store data corresponding to the number M of image lines may be used.

5 The range correction section 103 performs range
correction processing on the image data provided from
the memory controller 97 via the low path filter 101
using the white and black side reference values D_W and
 D_B calculated from the data corresponding to the number
M of image lines in the reference value calculating
10 section 100. As a result, the entire one page of
the document image is processed using a pair of the
reference values (D_W and D_B).

15 Thus, in the present invention, the image data
captured by the scanner section 4 is taken in the
reference value calculating section 100 where the
histogram creation is conducted. In parallel to such
a processing, the image data is taken in the memory,
and reading-out of the image data is delayed by a time
period required for the histogram creation (equal to
20 or less one page of a document). The reference value
(white side reference value) of a background reproduc-
tion and the reference value (black side reference
value) of a character reproduction which are the
reference values for range correction are determined
25 from the histogram created. Accordingly, it becomes
possible to perform an optimal range correction for
each document using image data corresponding to one

page of the document or less. Also, it becomes possible to perform an appropriate range correction and an appropriate image formation with one time scanning.

FIG. 6 is a flowchart showing an image processing operation according to a second embodiment of the present invention.

In the second embodiment, a calculation of a set of reference value for range correction is performed only one time, as shown in Step S16, after image data corresponding to the number M of image lines for calculating the reference values is taken in the reference value calculating section 100 and the density histogram corresponding to the number M of image lines is created. Also, the creation of the density histogram shown in Step S13 may be created using high-order several bits of the image data without use of the weighting coefficient shown in the first embodiment. The other steps are the same as those in the first embodiment.

As mentioned above, according to the present invention, appropriate range correction reference values are determined by document scanning of one time, and an automatic density adjustment and image formation are performed. Accordingly, an automatic density adjustment which allows a dark color reproduction of a light color character, removal of a background portion or the like can be performed and an even density

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100	